



PRODUCT DATA SHEET

Product: #156 --- Computer Stencil

Description: **High Tack Acrylic adhesive / Clear Polyester Liner.** High quality / durable stencil coated with an advanced water based pressure-sensitive adhesive. **Slot-hole pattern.** Rubber is trimmed back 1/2" along each edge for **IBM** cutters. #156 is designed and recommended for raw / unfinished wood, HDU foamboard, brick, and rough stone. Replaces #125 Stencil. Not intended for use on polished or painted surfaces.

Nominal Values:

| Adhesive | High Tack / Acrylic |
|--|---------------------|
| 180° Adhesion to Steel (oz/in of width) PSTC-1 | 30 |
| Tensile Strength (lbs/in of width) PSTC-31 | 7 |
| Elongation (% at break) PSTC-31 | 450 |
| Total Thickness (mils) PSTC-33 | 41 |

Product

Application: **Caution:** Aggressive acrylic adhesive may transfer to pre-treated or painted surface and/or may lift the grain of wood (esp. soft woods). Remove immediately after blasting whenever possible. #156 will not work on Gerber 30" plotter. (Recommend #116 for this machine).

Standard

Sizes: 30" x 10 yards.

NOTICE: While we believe them to be reliable, the statements and information herein are only for general guidance and are not warranties or guarantees for accuracy and completeness. The user must by test or otherwise determine suitability for his purpose. THERE IS NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE, Our standard terms and conditions of sale apply exclusively to all orders, and ALL LIABILITY FOR DAMAGES OF ANY KIND, INCLUDING CONSEQUENTIAL, EXCEEDING PURCHASE PRICE IS EXCLUDED. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

01-08