

PE-8

PRESERVATION TAPE

DESCRIPTION

PE-8 has a durable, moisture resistant PE (polyethylene) backing with a rubber-based pressure-sensitive adhesive. Bonds well to a variety of surfaces. Clean removal from a variety of gel-coated surfaces.

Designed to offer a high degree of conformability without excessive stretch. Stiffer backing makes it easier to handle in certain applications. UV resistance up to six months, depending upon conditions and surfaces.

PRODUCT APPLICATION

For patching, sealing, bundling and wrapping. For splicing and surface protection.

AVAILABLE SIZES

- 48mm x 33m
- 72mm x 33m
- 96mm x 33m
- 144mm x 33m



intertape polymer group™

3647 Cortez Road West | Bradenton, FL 34210 | USA

Customer Service: 800.IPG.8273 | 800.474.8273

Tape Technical Service: 877.447.4832

www.intertapepolymer.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 4/09

INTERTAPE POLYMER GROUP TECHNICAL DATA SHEET

PHYSICAL PROPERTIES

The following data are nominal values based on PSTC, ASTM and other standard test. The data should not be considered as specifications.

Backing	Polyethylene (PE) film
Color	White
Adhesive	Synthetic Rubber
Adhesion to Steel (oz/in of width) PSTC-1	75 (21 N/25mm)
Tensile Strength (lbs/in of width) PSTC-31	18 (79 N/25mm)
Total Thickness (mils) PSTC-33	9.0 (0.23mm)
Operation Temperature Resistance	20°F to 150°F (-7°C to 65°C)

