



PRODUCT DATA SHEET

Product: DCFA-32 --- Double-Coated PE Foam Tape

Description: Cross-linked high density polyethylene, closed cell foam coated on both sides (double-coated) with a high tack, permanent bonding Acrylic pressure-sensitive adhesive protected by an easy release treated 60# glassine (white) paper liner. High adhesion properties allows permanent bond to a variety of surfaces for mounting applications. **Color:** White

Nominal Values:	Backing	Closed Cell / Cross-linked PE Foam
	Adhesive	Acrylic
	Total Thickness w/o liner (Inch)	1/32" (0.8 mm)
	Density (PFC)	6.0
	Adhesion to Steel (oz/in width)	100 (27.4 N/25mm)
	Shear Adhesion (Hours) 1 kg / inch ²	> 100
	Service Temperature (Long Term)	-4°F ~ +140°F (-20°C ~ +60°C)

Product Application: Long term bonding. UV and chemical resistant. Mounting mirror and decorative tile, Nameplate / emblem mounting, Cushioning, Dampening Sound or Vibration, Gasketing / Sealing against moisture, dust, and light, Bonding Wire Harness Clips, Window glazing, Adhering vinyl and plastic trim, molded plastics, and any application that requires the joining of two surfaces.

Available length: 216 ft. (72 yards / 65.8m)

NOTICE: While we believe them to be reliable, the statements and information herein are only for general guidance and are not warranties or guarantees for accuracy and completeness. The user must by test or otherwise determine suitability for his purpose. THERE IS NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE, Our standard terms and conditions of sale apply exclusively to all orders, and ALL LIABILITY FOR DAMAGES OF ANY KIND, INCLUDING CONSEQUENTIAL, EXCEEDING PURCHASE PRICE IS EXCLUDED. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

09/04