



PRODUCT DATA SHEET

Product: DCFR-16--- Double-Coated PE Foam Tape

Description: Cross-linked high density polyethylene closed cell foam coated on both sides (double-coated) with a permanent bonding rubber pressure-sensitive adhesive protected by an easy release treated 60# (90 g/m²) white glassine paper liner. Very high adhesion properties allow immediate, permanent bond to a variety of surfaces for mounting applications. **Color:** White

Nominal Values:	Backing	Closed Cell / Cross-linked PE Foam
	Adhesive	Rubber (solvent cast)
	Total Thickness w/o liner (Inch)	1/16" (1.6 mm)
	Density (PFC)	4.0
	Adhesion to Steel (oz/in width)	> 113 (>3.2 kg/25mm)
	Shear Adhesion (Hours) 2 kg / inch ²	> 240
	Service Temperature	14°F ~ 140°F (-10°C ~ +60°C)

Product Application: Heavy-duty holding. Nameplate / emblem mounting, Cushioning, Dampening Sound or Vibration, Sealing against moisture, dust, and light, Bonding Wire Harness Clips, Window glazing, Adhering vinyl and plastic trim, molded plastics, and any application that requires the joining of two surfaces.

Available Length: 108 ft. (36 yards /32.9m)

NOTICE: While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must by test or otherwise determine suitability for his purpose. THERE IS NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE, Our standard terms and conditions of sale apply exclusively to all orders, and ALL LIABILITY FOR DAMAGES OF ANY KIND, INCLUDING CONSEQUENTIAL, EXCEEDING PURCHASE PRICE IS EXCLUDED. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

10/04