



**PRODUCT DATA SHEET**

**Product:** #DCP-20 --- Double-Coated Polyester

**Description:** Thin polyester film, coated on both sides with an aggressive acrylic pressure-sensitive adhesive. Excellent adhesion and shear properties. Good resistance to ultra-violet (UV) rays and most chemicals / solvents. Very good initial tack allowing immediate, permanent bond to a variety of surfaces. DCP-20 features an easy release treated 3 mil MOPP film liner (Pink). **Product is not repulpable.**

**Nominal Values:**

Backing	0.5 mil (12.7µ) PET Film
Adhesive	Solvent Acrylic (Clear)
Adhesion to Steel (oz/in of width)	66 (18 N/25mm)
Tensile Strength (lbs/in of width)	12 (53 N/25mm)
Elongation (% at break)	180
Total Thickness w/o liner (mils)	8.0 (0.20 mm)
Service Temperature	
Long Term	-4°F ~ +356°F
Short Term	(-20°C ~ 180°C) to +392°F (200°C)

**Product**

**Application:** Photograph (clear mounting), Nameplate mounting, Assembling outdoor displays, Splicing corrugated and paper, Mounting plastic trim, Bonding shrink film window insulation, and any application that requires the joining of two surfaces.

**Available**

**Length:** 60 yards (54.8 m)

**NOTICE:** While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must by test or otherwise determine suitability for his purpose. THERE IS NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE, Our standard terms and conditions of sale apply exclusively to all orders, and ALL LIABILITY FOR DAMAGES OF ANY KIND, INCLUDING CONSEQUENTIAL, EXCEEDING PURCHASE PRICE IS EXCLUDED. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

09/04