



PRODUCT DATA SHEET

Product: AC36 --- Medium Grade, Contractor Grade Duct Tape

Description: Polyethylene coated cloth tape with an aggressive natural rubber pressure-sensitive adhesive for improved adhesion and shear properties. Product is designed to answer the end-use / consumer need for an economical General-purpose duct tape. Meets HUD, BOCA, and L.A. County codes. Tested in accordance with UL-723

Nominal Values:	Backing	Polyethylene Coated Cloth
	Adhesion to Steel (oz/in of width) PSTC-1	50 (13.7 N/25mm)
	Quick Stick (oz/in of width) PSTC-5	
	To Steel	17 (4.7 N/25mm)
	Tensile Strength (lbs/in of width) PSTC-31	22 (96 N/25mm)
	Elongation (% at break) PSTC-31	23
	Thickness (mils) PSTC-33	11.0 (0.28 mm)
	Shear Adhesion (hours) 1" x 1" @ 1000g	Greater than 24 hours
	Colors	Silver and Black (printed or non-printed), and Teal (non-printed)
	Application Temperature Range	+40°F (4°C) to +90°F (32°C)
	Operational Temperature Range	+32°F (0°C) to +180°F (82°C)

Applications: HVAC Applications, Asbestos / Lead / Fiberglass Abatement, Exterminators, Weather Proofing, Gasket material for Flex-duct connections, Temporary Wrapping, and General Maintenance,

NOTICE: While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must by test or otherwise determine suitability for his purpose. THERE IS NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE, Our standard terms and conditions of sale apply exclusively to all orders, and ALL LIABILITY FOR DAMAGES OF ANY KIND, INCLUDING CONSEQUENTIAL, EXCEEDING PURCHASE PRICE IS EXCLUDED. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

02-08