



**PRODUCT DATA SHEET**

**Product:** PG-20 Masking Tape – Weatherable

**Description:** A weatherable masking tape utilizing an aluminized, black, saturated crepe paper backing to protect the especially formulated high temperature resistant adhesive from the effects of ultraviolet light. The product can be used in outdoor applications for periods of up to one month depending on the weather conditions and the surface to which the tape is applied. Available in silver only.

<b>Nominal Values:</b>	Backing	Aluminized Black Crepe Paper
	Adhesion to Steel (oz/in of width)	33 (9 N/25mm)
	Quick Stick (oz/in of width)	
	To Kraft	7 (1.9 N/25mm)
	To Steel	16 (4.4 N/25mm)
	Tensile Strength (lbs/in of width)	22 (96 N/25mm)
	Elongation (% at break)	8
	Thickness (mils)	6.8 (0.173 mm)

**Features:** Temperature resistant operating range: 50°F (10°C) to 325°F (163°C) for 20 to 40 minutes.

NOTICE: While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must by test or otherwise determine suitability for his purpose. THERE IS NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE, Our standard terms and conditions of sale apply exclusively to all orders, and ALL LIABILITY FOR DAMAGES OF ANY KIND, INCLUDING CONSEQUENTIAL, EXCEEDING PURCHASE PRICE IS EXCLUDED. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

07/03