



PRODUCT DATA SHEET

Product: PG-29 Masking Tape - General Purpose

Description: A smooth paper backed, low-tack, pressure-sensitive masking tape.

Nominal Values:	Backing	Fine Structured Crepe Paper
	Color	Natural
	Adhesive	Synthetic Rubber/Resin
	Adhesion to Steel (oz/in of width)	25 (6.8 N/25mm)
	Quick Stick (oz/in of width)	
	To Kraft	3 (0.8 N/25mm)
	To Steel	13 (3.6 N/25mm)
	Tensile Strength (lbs/in of width)	25 (109 N/25mm)
	Elongation (% at break)	10
	Thickness (mils)	6.8 (0.173 mm)

Product Application: Interior masking, (i.e. walls, woodwork and windows) for new home construction and home improvement. General purpose masking and protective masking. Can also be used for Wet strip automotive paint masking.

Features:
Smooth Crepe, Saturated Backing

Non-printable Release Coat

Synthetic Rubber/Resin Adhesive

Quarter Packed/Poly Wrapped

Advantages:
Smooth to the touch and easy to work with.
Straight, clean paint-break line.
Highly conformable and flexible.
Tear resistant / Solvent resistant.
Controlled unwind.
Resists paint flaking upon removal.
Good adhesion and holding power. Can be safely applied to a wide variety of surfaces (i.e., painted drywall, wooden trim, veneer paneling, etc.).
No loose rolls / Less damage in handling.
Cleaner looking product to operator.
Easy distribution from cartons.

NOTICE: While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must by test or otherwise determine suitability for his purpose. THERE IS NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE, Our standard terms and conditions of sale apply exclusively to all orders, and ALL LIABILITY FOR DAMAGES OF ANY KIND, INCLUDING CONSEQUENTIAL, EXCEEDING PURCHASE PRICE IS EXCLUDED. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

07/03