



**PRODUCT DATA SHEET**

**Product:** PG-56 - General Purpose, Medium Temperature, Premium Grade Masking

**Description:** A superior grade, general industrial pressure-sensitive masking tape having medium temperature capabilities. PG-56 can withstand exposure to forced drying conditions up to 250°F (120°C) for 30 minutes with warm to hot removal recommended. Excellent quick stick and holding properties. Designed for applications requiring transfer resistance in conjunction with a variety of paints and surfaces. Special release coat provides a ‘extra measure’ of moisture and solvent resistance. Not recommended for outdoor exposure.

<b>Nominal Values:</b>	Backing	Medium Crepe Paper
	Adhesive	Natural Rubber/Resin
	Adhesion to Steel (oz/in of width)	33 (9 N/25mm)
	Quick Stick (oz/in of width)	
	To Kraft	9 (2.5 N/25mm)
	To Steel	17 (4.6 N/25mm)
	Tensile Strength (lbs/in of width)	26 (114 N/25mm)
	Elongation (% at break)	9
	Thickness (mils)	6.4 (0.162 mm)

**Features:** Temperature resistant operating range: 40°F (4°C) to 250°F (120°C) for 30 minutes.

NOTICE: While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must by test or otherwise determine suitability for his purpose. THERE IS NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE, Our standard terms and conditions of sale apply exclusively to all orders, and ALL LIABILITY FOR DAMAGES OF ANY KIND, INCLUDING CONSEQUENTIAL, EXCEEDING PURCHASE PRICE IS EXCLUDED. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

08/04