



intertape polymer group

Product Code **T-226**

PRODUCT DATA SHEET

Product: T226 --- "BlastLite"

Description: IPG's answer to Vinyl. Specially formulated rubber provides impact resistance and natural flexibility allowing T226 to conform tightly around curves and uneven surfaces. High-Tack acrylic adhesive bonds quickly to clean surfaces. Uniform thickness / high quality / conformable / long-lasting / easy to use. Release treated paper liner permits easy tear by hand. Can also be cut by knife for precise fit.

Nominal Values:

Adhesive	Acrylic
Color	Tan
Adhesion to Steel (oz/in of width) PSTC-3	28 (7.6 N/25mm)
Tensile Strength (lbs/in of width) PSTC-31	3.0 (13 N/25mm)
Elongation (% at break) PSTC-31	250
Total Thickness (mils) PSTC-33	28 (0.71mm)

Product

Application: Superior surface protection and seal. Especially for use on raw wood, unprimed HDU, brick or unglazed tile.

Standard

Sizes: 15", 20", 25", 30" x 10 yards. Un-punched / Hand Cut and Friction Fed.

NOTICE: While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must by test or otherwise determine suitability for his purpose. THERE IS NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE, Our standard terms and conditions of sale apply exclusively to all orders, and ALL LIABILITY FOR DAMAGES OF ANY KIND, INCLUDING CONSEQUENTIAL, EXCEEDING PURCHASE PRICE IS EXCLUDED. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

01-08