

530

KRAFT UTILITY PAPER FLATBACK TAPE

INTERTAPE POLYMER GROUP TECHNICAL DATA SHEET

DESCRIPTION

Pressure sensitive, moisture resistant flatback with an aggressive blend natural/synthetic rubber adhesive designed to offer a positive, attractive seal and excellent adhesion to minimize carton sealing failures and prevent pilferage. Performs well under a wide range of temperature and humidity conditions. #530 is designed for use in applications where reduced weight can provide packaging material savings. Complies with Postal Regulation for Uninsured Packages. Product is not repulpable.

PRODUCT APPLICATIONS

Carton sealing, packaging, silk screening, picture framing, beaming/leasing, splicing, and tabbing

GOVERNMENT COMPLIANCE

PPP-T-42C, Type II
C.I.D. A-A-883B, Type II

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard test. The data should not be considered as specifications.

Backing	Kraft Flatback Paper
Adhesive	Natural / Synthetic Rubber
Adhesion to Steel (oz/in of width) PSTC-1	50 (13.7 N/25mm)
Tensile Strength (lbs/in of width) PSTC-31	40 (175 N/25mm)
Elongation (at break)	7%
Total Thickness (mils) PSTC-33	7.2 (0.18mm)
Color	Brown



3647 Cortez Road West | Bradenton, FL 34210 | USA
Customer Service: 800.IPG.8273 | 800.474.8273
Tape Technical Service: 877.447.4832
www.itape.com | info@itape.com



While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 11/10

