

341

EXTRA HEAVY DUTY CARTON SEALING TAPE

INTERTAPE POLYMER GROUP TECHNICAL DATA SHEET

DESCRIPTION

Rugged BOPP film, coated with a high grade, emulsion acrylic adhesive, for extra heavy duty box sealing. Provides reliable all-temperature box sealing performance in arctic cold or tropical heat, with controlled unwind to facilitate dispensing on manual or automatic box sealing machines, superior quick stick and fiber tear, high holding power to prevent 'flagging', excellent resistance to aging, weathering, UV light and yellowing.

PRODUCT APPLICATION

High performance, for heavy weight or bulky box sealing and other packaging applications, typically exposed to rougher shipping conditions and load stress.

GOVERNMENT COMPLIANCE

Conforms to the requirements of UPS, Parcel Post Air Freight and Motor Freight Classification Rule 222, and complies with the Federal Food Drug and Cosmetic Act, CFR Title 21, Subpart B, Par 175.105, which covers the use of pressure sensitive adhesives and tapes for indirect contact food packaging, such as box sealing.

PHYSICAL PROPERTIES

The following data are nominal values based on PSTC, ASTM and other standard test. The data should not be considered as specifications.

Backing (Cast BOPP film)	2.0 mil (0.0508 mm)
Tensile Strength ASTM D-3759	33 lb _f /in width (578 N/100mm)
Elongation (at break) ASTM D-3759	110%+
Adhesive	Emulsion Acrylic
Adhesion to Steel ASTM D-3330	36 oz/in (39 N/100 mm)
Total Thickness ASTM D-3652	3.0 mil (0.0762 mm)
Application Temperature Range	+32°F (0°C) to +150°F (49°C)
Operating Temperature Range	-30°F (-35°C) to +200°F (93°C)
Colors	Clear



3647 Cortez Road West | Bradenton, FL 34210 | USA
Customer Service: 800.IPG.8273 | 800.474.8273
Tape Technical Service: 877.447.4832
www.intertapepolymer.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 8/09

